

IMSA CABLE 19-1, #14 AWG, 25-CONDUCTOR				
CABLE #1	CABLE #2	CONDUCTOR COLOR		SIGNAL INTERVAL
		BASIC COLOR	TRACER STRIPE	
ø1	ø5	RED	WHITE	RED
		BLACK	WHITE	YELLOW
		GREEN	WHITE	GREEN
		BLACK	WHITE/RED	SPARE
ø2	ø6	RED	----	RED
		ORANGE	----	YELLOW
		GREEN	----	GREEN
ø3	ø7	BLACK	RED	RED
		ORANGE	RED	YELLOW
		BLUE	RED	GREEN
		WHITE	BLACK/RED	SPARE
ø4	ø8	RED	BLACK	RED
		ORANGE	BLACK	YELLOW
		GREEN	BLACK	GREEN
ø2 PED.	ø6 PED.	BLUE	----	WALK
		BLACK	----	DON'T WALK
		WHITE	BLACK	PUSH BUTTON
ø4 PED.	ø8 PED.	BLUE	WHITE	WALK
		RED	GREEN	DON'T WALK
		WHITE	RED	PUSH BUTTON
COMMON	COMMON	WHITE	----	P.B. COMMON
SPARE	SPARE	BLUE	BLACK	SPARE
SPARE	SPARE	RED	BLACK/WHITE	SPARE
SPARE	SPARE	GREEN	BLACK/WHITE	SPARE
SPARE	SPARE	ORANGE	GREEN	SPARE

IMSA CABLE 19-1, #14 AWG, 4 & 7-CONDUCTOR			
SIGNAL HEADS OUTSIDE MAST ARM & 5-SECTION		SIGNAL HEADS 3-SECTION	
7-CONDUCTOR CABLE		4-CONDUCTOR CABLE	
BASIC COLOR	SIGNAL INTERVAL	BASIC COLOR	SIGNAL INTERVAL
RED	RED	RED	RED
BLACK	YELLOW	BLACK	YELLOW
GREEN	GREEN	GREEN	GREEN
ORANGE	YELLOW ARROW	WHITE	VEH. COM.
BLUE	GREEN ARROW		
WHITE	VEH. COM.		
WHT/BLK TR	SPARE		
PEDESTRIAN HEADS		PUSH BUTTON	
4-CONDUCTOR CABLE		4-CONDUCTOR CABLE	
BASIC COLOR	SIGNAL INTERVAL	BASIC COLOR	SIGNAL INTERVAL
RED	DON'T WALK	RED	PUSH BUTTON
BLACK	SPARE	BLACK	SPARE
GREEN	WALK	GREEN	SPARE
WHITE	PED. COM	WHITE	P.B. COM.

PRE-EMPTION	
4-CONDUCTOR CABLE	
BASIC COLOR	CIRCUIT
YELLOW	A,B,C,D
ORANGE	26V
BLUE	GROUND
BARE	EARTH GROUND

NOTE:  
Pre-emption cable shall be M913 Strobecom Detector Cable or approved equal.

REV. 01/2017

